## NSN 4720-00-230-6516

A542a0

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-230-6516

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
4.000 inches
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, chloroprene and 2nd layer rubber impregnated woven fabric and 3rd layer helix wire coil and 4th layer rubber
impregnated woven fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
4.000 inches 2nd end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
360.000 inches excluding end fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nh-spcl 1st end
Specification Data:
81349-mil-h-17505 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: