

View Online at <https://aerobasegroup.com/nsn/4720-00-230-6576>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Tempurature Rating:**

-40.0 degrees fahrenheit single response

**Outside Diameter:**

1.188 inches

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded internal hose 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

900.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Thread Size:**

0.500 inches 2nd end

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

300.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Npsh 2nd end

**Specification Data:**

81348-zz-h-500 government specification

**Specification Or Standard:**

2 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0