

View Online at <https://aerobasegroup.com/nsn/4720-00-230-6576>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Tempurature Rating:

-40.0 degrees fahrenheit single response

Outside Diameter:

1.188 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal hose 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.500 inches 2nd end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

300.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Air single response

Thread Series Designator:

Npsh 2nd end

Specification Data:

81348-zz-h-500 government specification

Specification Or Standard:

2 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0