## NSN 4720-00-232-5648

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-232-5648 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.531 inches **Minimum Inside Bending Radius:** 2.500 inches **Connection Style:** Plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, chloroprene and 1st layer braided rayon cord **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.250 inches 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 36.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Npt 1st end

Shelf Life: N/a

## NSN 4720-00-232-5648

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0