Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-232-5649

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Fhread Direction:	
Right-hand 1st end	
nside Diameter:	
0.250 inches	
Fempurature Rating:	
40.0 degrees fahrenheit and 225.0 degrees fahrenheit single response	
Dutside Diameter:	
0.469 inches	
/inimum Inside Bending Radius:	
2.500 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Fhreaded internal tube 1st end	
Burst Test Pressure:	
600.0 pounds per square inch	
ayer Composition And Location:	
Duter layer molded rubber, synthetic and 1st layer spirally wrapped rayon fabric	
Aximum Operating Pressure:	
00.0 pounds per square inch	
Fhread Size:	
0.438 inches 1st end	
Seat Angle:	
5.0 degrees 1st end	
Duter Covering Environmental Protection:	
uel resistant and oil resistant and water resistant and weatherproof	
nside Surface Condition:	
Smooth	
leasuring Method And Length:	
3.250 inches	
ledia For Which Designed:	
Air and grease and hydraulic fluid and fuel/oil, hydrocarbon and water single resp	ponse
Thread Series Designator:	

NSN 4720-00-232-5649

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

