NSN 4720-00-232-9401



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-232-9401 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Tempurature Rating:** -100.0 degrees fahrenheit and 500.0 degrees fahrenheit single response **Outside Diameter:** 1.109 inches **Minimum Inside Bending Radius:** 7.380 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

NSN 4720-00-232-9401

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Me	thod And	Length:
56.000 inches	working	

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0