Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-232-9407

Cross Sectional Snape:         Round         Thread Class:         3b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.625 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.789 inches         Minimum Inside Bending Radius:         6.500 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thread Qi Per Inch (tpl):         12 1st end         Burst Test Pressure:         600.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1000.0 pounds per square inch         Electrostatic Test Pressure:         1000.0 pounds per square inch         Straight 2 st end         Straight 2 st end         Straight 2 st end         Straight 2 st end         Concettin Straight 2 st end         Straight 2 st end         Straight 2 st end<	Crease Continued Change
Tread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.625 linches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.739 linches Minimum Inside Bending Radius: 6.500 linches Connection Style: Solutient Iater 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Fatures Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Quer layer braided corrosion resistant steel wire Maximum Operating Pressure: 100.0 pounds per square inch Electrostatic st end Stard Steel Auger Engel St end Thread Steel 1.052 linches 1st end Steal Angle: 3.7.0 degrees 1st end Minimum Operating Pressure: 200.0 pounds per square inch Murder Steel St end Stard Steel Steal Angle: 3.7.0 degrees 1st end Murder Steel St end M	Cross Sectional Shape:
B ist end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.625 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.739 inches         Minimun Inside Bending Radius:         6.500 inches         Connection Style:         Solviel nut flare 1st end         End Connection Design:         Stright 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Threaded internal tube 1st end         Forsy Quy Per Inch (tpi):         12 1st end         Burst Test Pressure:         6000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximun Operating Pressure:         1000.0 pounds per square inch         Electaries         1000.0 pounds per square inch         Steries         1000.0 pounds per square inch         Charce         Steries Tist end         Steries Tist end         St	
Thread Direction: Right-hand 1st end Inside Diameter: O.625 inches Tempurature Rating: -55.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: O.789 inches Minimun Inside Bending Radius: O.789 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Features Provided: Electrostatic discharge capability Thread Q ty Per Inch (tpi): 12 1st end Burst Test Pressure: O00.0 pounds per square inch Cuer layer braided corrosion resistant steel wire Maximun Operating Pressure: 1.062 inches 1st end End Concetion Style: Outer layer Ist end Concetion Style: Cuer layer Ist end Cuer Cuerting Pressure: 1.060.0 pounds per square inch Cuer layer Ist end Cuer Cuerting Pressure: 1.062 inches 1st end Cuer Cuerting Pressure: 2.00.0 pounds per square inch Cuer Cuerting Pressure: 2.00.0 poun	
Right-hand 1st end         Inside Diameter:         0.625 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.789 inches         Minimum Inside Bending Radius:         6.500 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Threaded internal tube 1st end         Fust St Pressure:         6000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corosion resistant steel wire         Maximum Operating Pressure:         1000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corosion resistant steel wire         Maximum Operating Pressure:         100.0 pounds per square inch         Layer Composition And Location:         100.0 pounds per square inch         Muter Steel         1.052 inches 1st end         Seat Angle:         1.7.0 degrees	
Inside Diameter: 0.625 inches 0.625 inches 0.625 inches 0.625 inches 0.630 degrees fahrenheit single response and 450.0 degrees fahrenheit single response 0.000 Diameter: 0.789 inches 0.789 inches 0.789 inches 0.789 inches 0.780 inches 0.7	
Note of the second s	
Tempurture Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.789 inches Minimum Inside Bending Radius: 6.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Chread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant 2000.0 pounds per square inch Corrosion resistant 2000.0 pounds per square inch Corrosion resistant Steel wire Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant 2000.0 pounds per square inch 2000.0 pounds per square inch 2000.0 pounds per squ	
-6.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response         Outside Diameter:         0.789 inches         Minimum Inside Bending Radius:         6.500 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         6000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1000.0 pounds per square inch         Thread Size:         1.062 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Outer Covering Environmental Protection:         Corrosion resistant         300.0 pounds per square inch         Seat Angle:         37.0 degrees 1st end         Muter Covering Environmental Protection:         Corrosion resistant	
Outside Diameter:         0.789 inches         Minimum Inside Bending Radius:         6.500 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         6000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1000.0 pounds per square inch         Thread Size:         1.062 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Outer Covering Environmental Protection:         Corrosion resistant         Vacuum In Torr:         50.8         Inside Surface Condit	
0.789 inches Minimul Inside Bending Radius: 6.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant Corrosion	
Minimul Iside Bending Radius: 6.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Set Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Lograme: Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Outside Diameter:
6.500 inchesConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchEntread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchSeat Angle:2000.0 pounds per square inchCorrosion resistantSeat Angle:2000.0 pounds per square inchCorrosing Environmental Protection:Corrosion resistantSoure Covering Environmental Protection:Corrosion resistantVacuum In Tor:50.8Inside Surface Condition:	
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Minimum Inside Bending Radius:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Chread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Yacuum In Torr: 50.8	6.500 inches
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Currosion resistant 2000.0 pounds per square inch Maximum Currosion resistant Steel wire 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Yacuum In Tor: 50.8 Inside Surface Condition:	-
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Currosion resistant 2000.0 pounds per square inch Maximum Currosion resistant 2000.0 pounds per square inch Mydrostatic Test Pressure: 2000.0 pounds per square inch Cuter Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Swivel nut flare 1st end
Conection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Seat Angle: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant Maximum Correing Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	End Connection Design:
Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant Corrosion resistant Corrosion resistant Yacuum In Torr: 50.8 Inside Surface Condition:	Straight 1st end
Features Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchCorrosion resistant Protection:Corrosion resistant6000.0 pounds per square inchStatic Test Pressure:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchCotrosion resistantPressure:2000.0 pounds per square inchStatic Test Pressure:2000.0 pounds per square inch <td>Connection Type:</td>	Connection Type:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Threaded internal tube 1st end
Thready Qty Per Inch (tpi):12 1st endBurst Test Pressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchCorrosion resistant Steel Wire37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantYacuum In Torr:50.8Inside Surface Condition:	Features Provided:
12 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8	Electrostatic discharge capability
Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Thready Qty Per Inch (tpi):
6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	12 1st end
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:	Burst Test Pressure:
Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:	6000.0 pounds per square inch
Maximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:	Layer Composition And Location:
1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Outer layer braided corrosion resistant steel wire
Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Maximum Operating Pressure:
1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	1000.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	1.062 inches 1st end
Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Seat Angle:
2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	37.0 degrees 1st end
Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	Hydrostatic Test Pressure:
Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition:	2000.0 pounds per square inch
Vacuum In Torr: 50.8 Inside Surface Condition:	Outer Covering Environmental Protection:
50.8 Inside Surface Condition:	Corrosion resistant
Inside Surface Condition:	Vacuum In Torr:
	50.8
Smooth	Inside Surface Condition:
	Smooth



## Measuring Method And Length:

144.000 inches working

## Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A542a0