Nonmetallic Hose Assembly - Page 1 of 2



Noninetalle hose Assembly hage hor 2
View Online at https://aerobasegroup.com/nsn/4720-00-234-3973
Cross Sectional Shape:
Round
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.275 inches 1st end
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
6.000 inches
Exterior Color:
Black
Angle Between Rigid Elbow Fittings In Deg:
180.0
Flange Outside Diameter:
1.500 inches 1st end
Connection Style:
Plain w/ gasket groove (sae flanged head) 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
Connection Type:
Plain face flange 1st end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided fiber and outer layer molded rubber, synthetic and 1st layer braided fiber
Maximum Operating Pressure:
750.0 pounds per square inch
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Flow Angle:
45.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.500 inches working
Flange Style:
Round w/ out bolt holes 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Hydraulic fluid, water base and water single response

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0