

View Online at <https://aerobasegroup.com/nsn/4720-00-234-3974>

Cross Sectional Shape:

Round

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Bolt Circle Diameter:

2.519 inches 2nd end

Flange Thickness:

0.600 inches 2nd end

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

7.000 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

180.0

Bolt Hole Quantity:

2 2nd end

Flange Outside Diameter:

1.750 inches 1st end

Flange Length:

3.276 inches 2nd end

Flange Width:

2.130 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.400 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

2250.0 pounds per square inch

Layer Composition And Location:

2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord

Maximum Operating Pressure:

562.0 pounds per square inch

Hydrostatic Test Pressure:

1125.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.250 inches

Flange Style:

Round w/ out bolt holes 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0