NSN 4720-00-236-0876

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-236-0876 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.560 inches **Minimum Inside Bending Radius:** 0.750 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 800.0 pounds per square inch **Layer Composition And Location:** Outer layer braided fiber **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Outer Covering Environmental Protection:** Fire retardant

Inside Surface Condition:

Convoluted

Measuring Method And Length:

19.250 inches working

Special Features:

W/polyolefin chafing sleeve

Thread Series Designator:

Unf 1st end

NSN 4720-00-236-0876

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0