NSN 4720-00-236-2656

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-236-2656 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.516 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end Thready Qty Per Inch (tpi): 27 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and outer layer molded rubber **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.125 inches 1st end Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch

Outer Covering Environmental Protection: Abrasion resistant **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 301.750 inches **Special Features:** Reusable fittings

NSN 4720-00-236-2656

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Air and fuel/oil, hydrocarbon and water, fresh single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0