

View Online at <https://aerobasegroup.com/nsn/4720-00-236-2667>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.656 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

11000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, synthetic and 1st layer braided steel wire

**Maximum Operating Pressure:**

2750.0 pounds per square inch

**Thread Size:**

0.562 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

5500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

28.000 inches working

**Special Features:**

2nd end includes O-ring

**Media For Which Designed:**

Hydraulic fluid, water base and fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0