Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-236-6469

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.922 inches	
Minimum Inside Bending Radius:	
5.500 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
7000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided fabric and 2nd layer braided steel wire and 3rd layer braided f	fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:	
1750.0 pounds per square inch	
Thread Size:	
0.875 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Outer Covering Environmental Protection:	
Cold resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
117.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	

NSN 4720-00-236-6469

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0