NSN 4720-00-238-3671

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-238-3671

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.630 inches
Minimum Inside Bending Radius:
3.380 inches
Exterior Color:
Black
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
3200.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided synthetic cord
Maximum Operating Pressure:
800.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1600.0 pounds per square inch
Outer Covering Environmental Protection:
Fire retardant
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.375 inches
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-00-238-3671

Nonmetallic Hose Assembly - Page 2 of 2



Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0