

View Online at <https://aerobasegroup.com/nsn/4720-00-238-5370>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit single response

Outside Diameter:

0.484 inches

Minimum Inside Bending Radius:

8.500 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external tube 2nd end

Thready Qty Per Inch (tpi):

24 2nd end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord

Maximum Operating Pressure:

1125.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

30.0 degrees 2nd end

Outer Covering Environmental Protection:

Cold resistant and ozone resistant and salt water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns and unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0