NSN 4720-00-238-5370

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-238-5370

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response
Outside Diameter:
0.484 inches
Minimum Inside Bending Radius:
8.500 inches
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal and external tube 2nd end
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
4500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord
Maximum Operating Pressure:
1125.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
30.0 degrees 2nd end
Outer Covering Environmental Protection:
Cold resistant and ozone resistant and salt water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Uns and unf 2nd end

NSN 4720-00-238-5370

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0