## NSN 4720-00-241-4620

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-241-4620						
Cross Sectional Shape:						
Round						
Inside Diameter:						
2.500 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response						
Outside Diameter:						
3.125 inches						
Minimum Inside Bending Radius:						
14.000 inches						
Flange Outside Diameter:						
4.000 inches 2nd end						
Connection Style:						
Plain w/ gasket groove (sae flanged head) 2nd end						
End Flange Construction:						
Solid 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Plain face flange 2nd end						
Burst Test Pressure:						
250.0 pounds per square inch						
Layer Composition And Location:						
Outer layer molded rubber, synthetic and 1st layer spirally laid rayon cord						
Maximum Operating Pressure:						
65.0 pounds per square inch						
Flow Angle:						
37.0 degrees 2nd end						
Outer Covering Environmental Protection:						
Abrasion resistant and oil resistant and weatherproof						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
16.375 inches						
Flange Style:						
Round w/ out bolt holes 2nd end						
Special Features:						
Clamps furnished						
Media For Which Designed:						
Fuel/oil, hydrocarbon single response						
Shelf Life:						

N/a

## NSN 4720-00-241-4620

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0