

View Online at <https://aerobasegroup.com/nsn/4720-00-242-5375>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.313 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.672 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Hose Or Tubing Specification/std Data:**

Sae j517, 100r5-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Inverted flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Threaded external pipe 1st end

**Features Provided:**

Reusable end fittings

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

9000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided textile yarn

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

0.375 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

244.000 inches

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Nptf 1st end

**Specification Data:**

Sae j517, 100r5-81343 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0