Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-242-6574

····· -····· -····· -····· -···· -······
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.090 inches
Minimum Inside Bending Radius:
9.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nonskive
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
0.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 36.000 inches Media For Which Designed: Air and fuel/oil, hydrocarbon and water single response Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A542a0