

View Online at <https://aerobasegroup.com/nsn/4720-00-244-0895>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.296 inches and 0.328 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.532 inches and 0.593 inches

Minimum Inside Bending Radius:

2.750 inches

Exterior Color:

Natural

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

1100.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber and 1st layer braided cotton cord

Maximum Operating Pressure:

275.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

550.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and mildew resistant and oil resistant and ozone resistant and cold resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.670 inches and 13.730 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0