NSN 4720-00-245-7746

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-245-7746

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end Inside Diameter:
0.156 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Natural Communication of the C
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:

76.2

NSN 4720-00-245-7746

Nonmetallic Hose Assembly - Page 2 of 2



Fiig: A542a0