

View Online at <https://aerobasegroup.com/nsn/4720-00-246-2586>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.219 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.438 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant and fire resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

84.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unef 1st end

**Specification Or Standard:**

4 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0