

View Online at <https://aerobasegroup.com/nsn/4720-00-246-2862>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.125 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.482 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Black

**Connection Style:**

Inverted flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal and external tube 2nd end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

24 and 18 2nd end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

23.219 inches

**Media For Which Designed:**

Hydraulic fluid, water base and hydraulic fluid, phosphate-ester base and hydraulic fluid, silicate-ester base single response

**Thread Series Designator:**

Uns and uns 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0