

View Online at <https://aerobasegroup.com/nsn/4720-00-246-2862>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.482 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external tube 2nd end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

24 and 18 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.219 inches

Media For Which Designed:

Hydraulic fluid, water base and hydraulic fluid, phosphate-ester base and hydraulic fluid, silicate-ester base single response

Thread Series Designator:

Uns and uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0