

View Online at <https://aerobasegroup.com/nsn/4720-00-246-5334>

Cross Sectional Shape:

Round

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.438 inches 2nd end

Outside Diameter:

Between 1.469 inches and 1.531 inches

Exterior Color:

Black

Center To Center Distance Between Bolt Holes Along Width:

1.500 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

2.000 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.750 inches 2nd end

Flange Width:

2.250 inches 1st end

Connection Style:

Raised 2nd end

Bolt Hole Diameter:

0.469 inches 2nd end

Raised Face Diameter:

10.125 inches and 10.127 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided rayon cord and 2nd layer braided corrosion resistant steel wire

Maximum Operating Pressure:

600.0 pounds per square inch

Hydrostatic Test Pressure:

1250.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.500 inches excluding end fittings

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Bolt holes both ends counterbored 0.031 in. Deep by 0.656 in. Dia

Special Markings:

Metal identification tag attached with metal strap

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0