

View Online at <https://aerobasegroup.com/nsn/4720-00-246-5334>

**Cross Sectional Shape:**

Round

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Flange Thickness:**

0.438 inches 2nd end

**Outside Diameter:**

Between 1.469 inches and 1.531 inches

**Exterior Color:**

Black

**Center To Center Distance Between Bolt Holes Along Width:**

1.500 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

2.000 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.750 inches 2nd end

**Flange Width:**

2.250 inches 1st end

**Connection Style:**

Raised 2nd end

**Bolt Hole Diameter:**

0.469 inches 2nd end

**Raised Face Diameter:**

10.125 inches and 10.127 inches 1st end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

2500.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided rayon cord and 2nd layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

600.0 pounds per square inch

**Hydrostatic Test Pressure:**

1250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

22.500 inches excluding end fittings

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Bolt holes both ends counterbored 0.031 in. Deep by 0.656 in. Dia

**Special Markings:**

Metal identification tag attached with metal strap

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0