

View Online at <https://aerobasegroup.com/nsn/4720-00-246-5338>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 0.844 inches and 0.906 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Flange Thickness:**

0.438 inches 2nd end

**Outside Diameter:**

Between 1.203 inches and 1.265 inches

**Minimum Inside Bending Radius:**

7.375 inches

**Exterior Color:**

Black

**Center To Center Distance Between Bolt Holes Along Width:**

0.812 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

2.000 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.750 inches 2nd end

**Flange Width:**

1.562 inches 2nd end

**Connection Style:**

Raised 2nd end

**Bolt Hole Diameter:**

0.469 inches 2nd end

**Raised Face Height:**

0.062 inches and 0.064 inches 2nd end

**Raised Face Diameter:**

1.185 inches and 1.187 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

3200.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord

**Maximum Operating Pressure:**

800.0 pounds per square inch

**Hydrostatic Test Pressure:**

1600.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

87.750 inches excluding end fittings and 88.250 inches excluding end fittings

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Microinch finish of 63 on both raised faces; bolt holes counterbore 0.031 in deep by 0.656 in dia

**Special Markings:**

Metal identification tag attached with metal strap

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0