

| NSN 4720-00-248-0123 |
|---|
| Nonmetallic Hose Assembly - Page 1 of 2 |
| View Online at https://aerobasegroup.com/nsn/4720-00-248-0123 |
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.312 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Exterior Color: |
| Natural |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Vacuum In Torr: |
| 50.8 |
| la side Ovurfe e e O e a ditie a c |

Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 11.750 inches working **Special Features:** Nuts drilled for lockwire **Thread Series Designator:** Unjf 1st end **Specification Data:** 96906-ms8000 government standard Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0