## NSN 4720-00-248-0262

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-248-0262

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.188 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.500 inches  |
| Minimum Inside Bending Radius:  |
| 3.500 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| Layer Composition And Location:                                       |
| Outer layer molded rubber and 1st layer braided steel wire            |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.438 inches 1st end  |
| Seat Angle:   |
| 45.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Outer Covering Environmental Protection:                              |
| Oil resistant and weatherproof  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 58.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response                                 |
| Thread Series Designator:   |
| Unf 1st end   |

## NSN 4720-00-248-0262

Nonmetallic Hose Assembly - Page 2 of 2



| $\sim$ |    |    |     |   |
|--------|----|----|-----|---|
| •      | no | 11 | ife | • |
|        |    |    |     |   |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0