NSN 4720-00-248-8976

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-00-248-8976 |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.340 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.550 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| Exterior Color: |
| Natural |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |

3000.0 pounds per square inch Flow Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

NSN 4720-00-248-8976

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

14.750 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0