NSN 4720-00-249-5109

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:

Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-249-5109

Right-hand 1st end
Inside Diameter:
0.485 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.710 inches
Minimum Inside Bending Radius:
3.250 inches
Angle Between Rigid Elbow Fittings In Deg:
45.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 1st end
Outer Covering Environmental Protection:
Corrosion resistant

NSN 4720-00-249-5109

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
32.250 inches working
Thread Series Designator:
Unjf 1st end
Specification Data:
81343-as118 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0