

NSN 4720-00-251-1277 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-251-1277 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end

Thread Direction: Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.446 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Natural **Connection Style:**

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

NSN 4720-00-251-1277

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
16.500 inches working
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms8000 government standard
Specification Or Standard:
6 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0