

View Online at <https://aerobasegroup.com/nsn/4720-00-253-3487>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.681 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

1.070 inches

Minimum Inside Bending Radius:

7.750 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Elbow 2nd end

End Fitting Component And Material:

Socket steel comp 304 2nd end

Connection Type:

Threaded external tube 2nd end

Features Provided:

Nuts drilled for lockwire

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

9000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer spirally wrapped corrosion resistant steel fabric

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.286 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0