Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-253-9005

Cross Sectional Shape:	
Round	
hread Class:	
b 1st end	
hread Direction:	
light-hand 1st end	
nside Diameter:	
.188 inches	
empurature Rating:	
65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Dutside Diameter:	
.516 inches	
Iinimum Inside Bending Radius:	
.000 inches	
Connection Style:	
wivel nut flare 1st end	
nd Connection Design:	
Straight 1st end	
Connection Type:	
hreaded internal tube 1st end	
Burst Test Pressure:	
2000.0 pounds per square inch	
ayer Composition And Location:	
nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord and	1 1st layer braided cotton cord
laximum Operating Pressure:	
000.0 pounds per square inch	
hread Size:	
.438 inches 1st end	
Seat Angle:	
7.0 degrees 1st end	
lydrostatic Test Pressure:	
000.0 pounds per square inch	
Outer Covering Environmental Protection:	
fildew resistant and oil resistant	
acuum In Torr:	
0.8	
nside Surface Condition:	
Smooth	
leasuring Method And Length:	
1.500 inches working	
ledia For Which Designed:	
uel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0