

View Online at <https://aerobasegroup.com/nsn/4720-00-254-5416>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.250 inches and 0.450 inches

Temperature Rating:

-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Outside Diameter:

0.450 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Green

End Application:

An/alq-119

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

Outer layer spirally wrapped polyamide fabric and 1st layer spirally wrapped polytetrafluoroethylene impregnated glass fiber

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Heat resistant and cold resistant and salt water resistant and vibration resistant

Inside Surface Condition:

Convuluted

Measuring Method And Length:

9.875 inches working and 10.125 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0