Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-254-5783

Cross Sectional Shape:	
Round	
Thread	d Class:
2b 1st	end
Thread	d Direction:
Right-h	hand 1st end
Inside	Diameter:
0.375 i	nches
Tempu	Irature Rating:
-40.0 d	legrees fahrenheit and 200.0 degrees fahrenheit single response
Outsid	le Diameter:
0.630 i	nches
Minim	um Inside Bending Radius:
2.000 i	nches
Exterio	or Color:
Black	
Conne	ction Style:
Swivel	nut flare 1st end
End Co	onnection Design:
Straigh	at 1st end
Conne	ection Type:
Thread	led internal tube 1st end
Thread	dy Qty Per Inch (tpi):
16 1st	end
Burst	Test Pressure:
9000.0	pounds per square inch
Layer	Composition And Location:
Outer I	ayer molded polyurethane and 1st layer braided fiber
Maxim	um Operating Pressure:
2250.0	pounds per square inch
Thread	d Size:
0.750 i	nches 1st end
Seat A	ngle:
37.0 de	egrees 1st end
Hydro	static Test Pressure:
4500.0	pounds per square inch
Outer	Covering Environmental Protection:
Oil resi	istant
Inside	Surface Condition:
Smoot	h
Measu	ring Method And Length:
252.00	0 inches

NSN 4720-00-254-5783

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:

W/reusable fittings

Media For Which Designed:

Air and fuel/oil, hydrocarbon and refrigerant 12 single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0