Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



Nonmetallic Hose Assembly - Page 1 of 2		Group
View Online at https://aerobasegroup.com/nsn/4720-00-254-5928		
Cross Sectional Shape:		
Round		
Thread Class:		
2b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.250 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response		
Outside Diameter:		
0.690 inches		
Minimum Inside Bending Radius:		
4.000 inches		
Exterior Color:		
Black		
Connection Style:		
Swivel nut flare 2nd end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Burst Test Pressure:		
20000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided steel wire and 2nd layer braided steel wire and 3rd layer rubber impregnated cotton fabric and out	er layer mold	led rubber,
synthetic		
Maximum Operating Pressure:		
5000.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
37.0 degrees 2nd end		
Flow Angle:		
45.0 degrees 2nd end		
Outer Covering Environmental Protection:		
Oil resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
13.500 inches working		
Media For Which Designed:		

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

