

View Online at <https://aerobasegroup.com/nsn/4720-00-255-7812>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.852 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

1.390 inches

Minimum Inside Bending Radius:

9.625 inches

Hose Or Tubing Specification/std Data:

Sae as604, size 16081343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.500 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, tetrafluoroethylene

Thread Series Designator:

Unj 1st end

Specification Data:

Sae as604, size 16081343 national std/spec and 81343-as604 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0