NSN 4720-00-255-7820

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-255-7820 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.343 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 7000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

6.500 inches working

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

NSN 4720-00-255-7820

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0