## NSN 4720-00-258-1783

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-258-1783

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
9.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and 3rd layer molded rubber, synthetic and 1st layer braided wire
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
1.462 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:

Smooth

## NSN 4720-00-258-1783

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length: 120.000 inches working Inside Diameter Hose Accommodated: 0.750 inches 1st end Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A542a0