NSN 4720-00-258-9938

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-258-9938

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.406 inches |
| Outside Diameter: |
| 0.562 inches |
| Angle Between Rigid Elbow Fittings In Deg: |
| 90.0 |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Elbow 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Thread Size: |
| 0.750 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 9.250 inches working |
| Supplementary Features: |
| This item has been reviewed for asbestos material. The current approved source, 1p322, has indicated their part number contained |
| asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984 |
| Thread Series Designator: |
| Unjf 1st end |
| Specification Data: |
| 73342-6877203 manufacturers source control |
| Shelf Life: |

N/a

NSN 4720-00-258-9938

Nonmetallic Hose Assembly - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0