NSN 4720-00-262-9302

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-262-9302 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.344 inches **Outside Diameter:** 0.766 inches **Minimum Inside Bending Radius:** 5.000 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Unthreaded external tube 2nd end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, chloroprene and 1st layer braided wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end **Outer Covering Environmental Protection:** Oil resistant and ozone resistant and cold resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 32.000 inches working **Outside Diameter Tube Accommodated:** 0.375 inches 2nd end Media For Which Designed: Hydraulic fluid single response **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

NSN 4720-00-262-9302

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0