

View Online at <https://aerobasegroup.com/nsn/4720-00-269-7052>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.212 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

Between 0.360 inches and 0.390 inches

Minimum Inside Bending Radius:

1.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant and fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.625 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as153 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0