NSN 4720-00-269-7656

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-269-7656

Round					
Thread Class:					
2b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.312 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.565 inches					
Minimum Inside Bending Radius:					
4.500 inches					
Exterior Color:					
Natural					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Reusable end fittings					
Burst Test Pressure:					
10000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer molded plastic and 1st layer braided polyester cord					
Maximum Operating Pressure:					
2500.0 pounds per square inch					
Thread Size:					
0.562 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
5000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Hydraulic solution resistant and weatherproof					
Inside Surface Condition:					

92.500 inches

Measuring Method And Length:

Smooth

NSN 4720-00-269-7656

Nonmetallic Hose Assembly - Page 2 of 2



	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0