Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-269-7659

Cros	s Sectional Shape:
Roun	d
Threa	ad Class:
2b 1s	t end
Threa	ad Direction:
Right	hand 1st end
Insid	e Diameter:
0.313	inches
Temp	purature Rating:
-40.0	degrees fahrenheit and 200.0 degrees fahrenheit single response
Outsi	de Diameter:
0.540	inches
Minin	num Inside Bending Radius:
4.500	inches
Exter	ior Color:
Black	
Conn	ection Style:
Swive	el nut flare 1st end
End (Connection Design:
Straig	ht 1st end
Conn	ection Type:
Threa	ded internal tube 1st end
Burst	Test Pressure:
10000	0.0 pounds per square inch
Laye	Composition And Location:
2nd la	ayer braided synthetic cord and outer layer molded plastic and 1st layer molded plastic
Maxiı	num Operating Pressure:
2500.	0 pounds per square inch
Threa	ad Size:
0.562	inches 1st end
Seat	Angle:
37.0 (degrees 1st end
Hydro	ostatic Test Pressure:
5000.	0 pounds per square inch
Insid	e Surface Condition:
Smoc	th
Meas	uring Method And Length:
23.50	0 inches
Threa	ad Series Designator:
Unf 1	st end
Shelf	Life:
N/a	

NSN 4720-00-269-7659

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0