

View Online at <https://aerobasegroup.com/nsn/4720-00-270-6331>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-3992, type 1, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Thready Qty Per Inch (tpi):**

18 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

900.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene

**First End Fitting/component And Material:**

Complete fitting-brass, alloy qq-b626, comp 360

**Thread Size:**

0.250 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Hydrostatic Test Pressure:**

450.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and mildew resistant and ozone resistant and cold resistant and fuel resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

115.000 inches

**Special Features:**

Inner conveying tube material-rubber; solid outer cover design, external support both ends complete fitting-brass, alloy qq-b626, comp 360

**Thread Series Designator:**

Nptf 1st end

**Specification Data:**

Mil-h-3992, type 1, class 1 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-3992 spec.