

View Online at <https://aerobasegroup.com/nsn/4720-00-270-7942>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.219 inches

Temperature Rating:

-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response

Outside Diameter:

0.625 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene and 1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

72.000 inches working

Media For Which Designed:

Carbon dioxide and hydraulic fluid single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms28762 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0