

View Online at <https://aerobasegroup.com/nsn/4720-00-273-2563>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.750 inches

**Tempurature Rating:**

-40.0 degrees fahrenheit single response

**Outside Diameter:**

1.375 inches

**Quick Disconnect Size:**

0.750 inches 1st end

**Connection Style:**

Universal 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Universal quick disconnect 1st end

**Burst Test Pressure:**

700.0 pounds per square inch

**Layer Composition And Location:**

1st layer rubber impregnated cotton fabric and 2nd layer rubber impregnated cotton fabric and 3rd layer rubber impregnated cotton fabric and 4th layer braided cotton cord and 5th layer braided cotton cord and 6th layer braided cotton cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

125.0 pounds per square inch

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches excluding end fittings

**Media For Which Designed:**

Air single response

**Specification Data:**

81348-zz-h-500 government specification

**Specification Or Standard:**

1 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0