## NSN 4720-00-273-9886

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-273-9886

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Left-hand 1st end   |
| Inside Diameter:  |
| 0.312 inches  |
| Tempurature Rating:   |
| -20.0 degrees fahrenheit single response  |
| Outside Diameter:   |
| 0.656 inches  |
| Exterior Color:   |
| Red   |
| Connection Style:   |
| Swivel nut, gas 1st end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal gas cylinder 1st end  |
| Thready Qty Per Inch (tpi):   |
| 18 1st end  |
| Burst Test Pressure:  |
| 700.0 pounds per square inch  |
| Layer Composition And Location:   |
| 1st layer braided synthetic cord and 1st layer braided cotton cord or 2nd layer braided synthetic cord and 2nd layer braided cotton cord or |
| outer layer molded rubber, synthetic and outer layer molded rubber, natural   |
| Thread Size:  |
| 0.562 inches 1st end  |
| Hydrostatic Test Pressure:  |
| 250.0 pounds per square inch  |
| Outer Covering Environmental Protection:  |
| Abrasion resistant  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 600.000 inches excluding end fittings   |
| Seat Radius:  |
| 0.196 inches 1st end  |
| Special Markings:   |
| Acet-hyd  |

Acetylene single response

Media For Which Designed:

## NSN 4720-00-273-9886

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Des | igna | tor |
|--------|--------|-----|------|-----|
|--------|--------|-----|------|-----|

Unf 1st end

**Specification Or Standard:** 

S type and r grade

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0