NSN 4720-00-273-9886

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-273-9886

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Left-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-20.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Exterior Color:
Red
Connection Style:
Swivel nut, gas 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal gas cylinder 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and 1st layer braided cotton cord or 2nd layer braided synthetic cord and 2nd layer braided cotton cord or
outer layer molded rubber, synthetic and outer layer molded rubber, natural
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
600.000 inches excluding end fittings
Seat Radius:
0.196 inches 1st end
Special Markings:
Acet-hyd

Acetylene single response

Media For Which Designed:

NSN 4720-00-273-9886

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Des	igna	tor
--------	--------	-----	------	-----

Unf 1st end

Specification Or Standard:

S type and r grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0